



Poles	Dimension In. (mm)	
	A	B
2	3.96	7.92
3	7.92	11.92
4	11.88	15.84
5	15.84	19.84
6	19.80	23.80
7	23.76	27.88
8	27.72	31.74
9	31.68	35.86
10	35.64	39.90
11	39.60	43.84
12	43.56	47.92
13	47.52	51.72
14	51.48	55.92

**ORDER INFORMATION**

Contact No.  -   Contact Type  P: Non Distribution Function  S: Straight Contact Plating  T: Tin S: Selective Gold G: Gold Flash Insulator Color  W: White

Fill It With "0"   Fill It With "0"

**玄茂科技股份有限公司**  
**HSUAN MAO TECHNOLOGY CO., LTD.**

制表日: 2002/12/04

DRAWING. APPROVED

*Jame*

UNIT  
MM

APPD. CKD.

SCALE  
3:1

TOLERANCE  
± 0.3

PART NAME  
VH3.96 WAFER 180°

PART NO.  
W3966-XXPSTW00

REV.  
A

**SPECIFICATION**

Voltage Rating: 250V AC/DC  
Current Rating: 5A AC/DC  
Temperature Range: -25 ° C ~+85 ° C  
Contact Resistance: 20 Milliohms Max.  
Insulation Resistance: 1,000 Megohms Min.  
Dielectric Withstanding Voltage: 1,500V AC/DC/Minute.  
Material: Nylon 66, UL94V-0  
Color: White  
Pin: Brass, Tin Plated