


| | |
|---------------------|-----------------------------|
| TAB SIZE | 6,3 x 0,80 |
| WIRE SIZE | 0,50 - 1,00 mm ² |
| MATERIAL | CuZn |
| PLATING | Sn |
| MAXIMAL TEMPERATURE | 120 °C |



TEST RESULTS

INSERTION / WITHDRAWAL FORCE

| | 1. INSERTION | 1. WITHDRAWAL | 6. WITHDRAWAL |
|----------------|--------------|---------------|---------------|
| TS EN 61210 | 80 N max. | - | 18 N min. |
| HATKO | 80 N max. | - | 18 N min. |
| Typical Values | 21 N | 33 N | 27 N |

CRIMP PULL-OUT FORCE

| | 1. PULL OUT FORCE | | |
|----------------|----------------------|----------------------|----------------------|
| | 0,50 mm ² | 0,75 mm ² | 1,00 mm ² |
| TS EN 61210 | 56 N min. | 84 N min. | 108 N min. |
| HATKO | 56 N min. | 84 N min. | 108 N min. |
| Typical Values | 129 N | 150 N | 214 N |

CRIMP MEASUREMENTS

| | HEIGHT | | WIDTH | |
|----------------------|------------|------------|------------|------------|
| | WIRE | INSULATOR | WIRE | INSULATOR |
| 0,50 mm ² | 1,40 ±0,04 | 2,41 ±0,05 | 2,55 ±0,05 | 3,55 ±0,05 |
| 0,75 mm ² | 1,50 ±0,04 | 2,45 ±0,05 | 2,55 ±0,05 | 3,55 ±0,05 |
| 1,00 mm ² | 1,58 ±0,04 | 2,47 ±0,05 | 2,55 ±0,05 | 3,57 ±0,05 |

| | CURRENT CARRYING CAPACITY Max. A | AMBIENT TEMPERATURE °C |
|----------------------|-------------------------------------|---------------------------|
| 0,50 mm ² | 10 | 75 |
| 0,75 mm ² | 16 | 40 |
| 1,00 mm ² | 18 | 40 |

PREP.: TURAN KELEŞ

CON.: HUSEYİN DOĞAN