



NOTES
 * Poles:2-18
 * Material:Insulator:PBT UL94V-0 BLACK
 * Contact:0.64mm(.025") square pin,brass,gold plated

Specifications
 * Current rating: 2.5A AC, DC
 * Voltage rating: 250V AC, DC
 * Temperature range: -25°C~+85°C
 * Insulation resistance: 1,000MΩ min.
 * Withstand voltage: 600 AC/minute
 * Applicable PC board thickness: .063" (1.6mm)
 * Endure under max. 240°C 5SECS.

CIRCUITS	DIMENSION mm	
	A	B
2	2.54	7.62
3	5.08	10.16
4	7.62	12.70
5	10.16	15.24
6	12.70	17.78
7	15.24	20.32
8	17.78	22.86
9	20.32	25.40
10	22.86	27.94
11	25.40	30.48
12	27.94	33.02
13	30.48	35.56
14	33.02	38.10
15	35.56	40.64
16	38.10	43.18
17	40.64	45.72
18	43.18	48.26

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY		TOLERANCE X. ±0.5 X.X ±0.25 X.XX ±0.2 X.XXX ±0.08	PART NAME 品名 CD ROM 2.54mm XXP W/O LOCATING PEG GOLD PLATED BLACK COLOR
DWG. 製圖 KAREN	SCALE 比例 參考	UNIT 單位 MM	PART NO. 料號 W7166-XXPXGB00R
DATE 制表日 2012/06/26	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A4	REV. 版本 A

