



MATERIAL & FINISH

SHELL

Zinc plated .Tin plated or nickel plated steel

CONTACT (Stamp)

Brass or phosphor bronze

Gold plated over nickel

Position	A± 0.1	B± 0.1	C± 0.1	D± 0.1	E± 0.1
09F	16.33	24.99	30.81	1.0	19.28
15F	24.66	33.32	39.14	1.0	27.51
19F	30.07	38.94	44.49	1.0	32.86
23F	35.41	44.27	50.27	1.0	38.51
25F	38.38	47.04	53.04	1.0	41.43
37F	54.84	63.50	69.32	1.0	57.71
50F	52.43	61.12	66.93	1.0	55.32

ORDER INFORMATION

Contact No.	Contact Type	Mounting Option	Accessories	Shell Plating	Contact Plating	Others
C0540 - <input type="text" value="09"/>	<input type="text" value="F"/>	<input type="text" value="A"/>	<input type="text" value="A"/>	<input type="text" value="T"/>	<input type="text" value="G"/>	<input type="text" value="B"/>
09 15 19 23 25 37 50	F: Female	A: Throught Hole	A: Non Accessories	T: Tin N: Nickel Z: Zinc(Chromatic)	S: Selective Gold G: Gold Flash A: Gold 5u" B: Gold 10u" C: Gold 15u" D: Gold 30u"	B: Black Insulator W: White Insulator L: Blue Insulator G: Grey Insulator

玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

制表日: 2002/12/04	DRAWING.	APPROVED
	kevin	

UNIT		SCALE	PART NAME	
MM		2 : 1	D-Sub Solder Type Female	
APPD.	CKD.	TOLERANCE	PART NO.	REV.
		± 0.3	C0540-XXFAAXXX	A