



SPECIFICATIONS

Electrical

Current Rating: 1A AC, DC

Voltage Rating: 100V AC/ max.

Operating Temp.: -25°C ~ +85°C

Insulation Resistance: 500MΩ/ min.

Dielectric Withstanding Voltage: 500V AC/ min.

Contact Resistance: 20mΩ/ max.

Material: PBT, UL94V-0

Poles	Dimension (mm)		
	A	B	C
2	1.25	2.72	5.72
3	2.50	3.97	6.97
5	5.00	6.47	9.47
6	6.25	7.72	10.72
7	7.50	8.97	11.97
9	10.00	11.47	14.47
14	16.25	17.72	20.72
15	17.50	18.97	21.97
20	23.75	25.22	28.22
30	36.25	37.72	40.72

ORDER INFORMATION

H1257 -

Contact No.

30

2.3.5.6.7.9
14.15.20.30

Contact Type

P

P: Non Distribution

Insulator Color

W

W: White

0

Fill It With '0'

0

Fill It With '0'

0

Fill It With '0'

0

Fill It With '0'

玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

制表日: 2002/12/04

DRAWING.

Jane

APPROVED

UNIT

MM

APPD.

CKD.

SCALE

3:1

TOLERANCE

± 0.3

PART NAME

MX1.25mm HOUSING

PART NO.

H1257-XXPW0000

REV.

A