



MATERIAL
 INSULATOR: PBT&GLASS-FIBER REINFORCED UL94V-0
 CONTACT: BRASS OR PHOSPHOR BRONZE GOLD FLASH OVER NICKEL
SPECIFICATION
 CONTACT SPACING: 2.00mm grid
 CURRENT RATING: 1 AMP DC
 CONTACT RESISTANCE: 30m OHMS MAX AT 6V DC 0.3A
 INSULATION RESISTANCE: 1000M OHMS MIN AT 500V DC
 OPERATING TEMPERATURE: -55 °C +105°C

| SHELL SIZE | A±0.20 | B±0.20 | C±0.20 |
|------------|--------|--------|--------|
| 6P | 11.14 | 4.00 | 5.00 |
| 8P | 13.14 | 6.00 | 7.00 |
| 10P | 15.14 | 8.00 | 9.00 |
| 14P | 19.14 | 12.00 | 13.00 |
| 16P | 21.14 | 14.00 | 15.00 |
| 18P | 23.14 | 16.00 | 17.00 |
| 20P | 25.14 | 18.00 | 19.00 |
| 22P | 27.14 | 20.00 | 21.00 |
| 24P | 29.14 | 22.00 | 23.00 |
| 26P | 31.14 | 24.00 | 25.00 |
| 28P | 33.14 | 26.00 | 27.00 |
| 34P | 39.14 | 32.00 | 33.00 |
| 36P | 41.14 | 34.00 | 35.00 |
| 38P | 43.14 | 36.00 | 37.00 |
| 40P | 45.14 | 38.00 | 39.00 |
| 44P | 49.14 | 42.00 | 43.00 |
| 48P | 53.14 | 46.00 | 47.00 |
| 50P | 55.14 | 48.00 | 49.00 |
| 54P | 59.14 | 52.00 | 53.00 |
| 56P | 61.14 | 54.00 | 55.00 |
| 60P | 65.14 | 58.00 | 59.00 |
| 62P | 67.14 | 60.00 | 61.00 |
| 64P | 69.14 | 62.00 | 63.00 |
| 68P | 73.14 | 66.00 | 67.00 |

玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

| UNIT | | SCALE | | PART NAME | |
|-------|------|-----------|----------------|----------------------|--|
| MM | | 2:1 | | 2.0 X 2.0 IDC Socket | |
| APPD. | CKD. | TOLERANCE | PART NO. | REV. | |
| | | ±0.3 | C9200-XXYYSB00 | A | |

制表日: 2004/1/04

DRAWING. APPROVED
kevin