


TAB SIZE	2,8 x 0,80
WIRE SIZE	0,50 - 1,00 mm <sup>2</sup>
MATERIAL	CuZn
PLATING	-
MAXIMAL TEMPERATURE	110 °C



**TEST RESULTS**

**INSERTION / WITHDRAWAL FORCE**

	1. INSERTION	1. WITHDRAWAL	6. WITHDRAWAL
TS EN 61210	53 N max.	-	5 N min.
HATKO	53 N max.	-	5 N min.
Typical Values	30 N	-	24 N

**CRIMP PULL-OUT FORCE**

	1. PULL OUT FORCE		
	0,50 mm <sup>2</sup>	0,75 mm <sup>2</sup>	1,00 mm <sup>2</sup>
TS EN 61210	56 N min.	84 N min.	108 N min.
HATKO	56 N min.	84 N min.	108 N min.
Typical Values	118 N	145 N	155 N

**CRIMP MEASUREMENTS**

	HEIGHT		WIDTH	
	WIRE	INSULATOR	WIRE	INSULATOR
0,50 mm <sup>2</sup>	1,18 ±0,04	2,23 ±0,05	2,20 ±0,05	3,24 ±0,05
0,75 mm <sup>2</sup>	1,25 ±0,04	2,28 ±0,05	2,22 ±0,05	3,24 ±0,05
1,00 mm <sup>2</sup>	1,32 ±0,04	2,33 ±0,05	2,24 ±0,05	3,25 ±0,05

	CURRENT CARRYING CAPACITY Max. A	AMBIENT TEMPERATURE °C
0,50 mm <sup>2</sup>	8	60
0,75 mm <sup>2</sup>	8	65
1,00 mm <sup>2</sup>	8	70

PREP.: TURAN KELEŞ

CON.: HUSEYİN DOĞAN